

Press fit pins are retained in an assembly by the frictional forces between the pin and its mating host component. These forces are a product of the coefficient of friction between the mating materials/coatings, and the interference fit between the pin and its host component.

There are two general categories of press fit pins; solid pins and spring pins. Solid pins, such as ground dowels and knurled pins, are retained by deforming the host material. Springs pins retain themselves by compressing to conform to the hole.

Successful installation and retention of press fit pins is greatly effected by the quality of the hole in the host component. Recommended hole sizes vary with the type of pin chosen for an assembly, which indirectly determines the hole preparation process. Generally, tighter hole tolerances require more expensive hole preparation.

This paper addresses the hole preparation processes required to successfully install and retain commonly used press fit pins. The pins evaluated in this document are listed below, in order of increasing recommended hole tolerance.

1. Ground Dowels & Straight Pins
2. Knurled & Grooved Pins
3. Slotted Spring Pins
4. Coiled Spring Pins



1. Ground Dowels & Straight Pins

Ground dowels and straight pins are solid cylindrical pins that normally have chamfered ends. The pins are retained in the assembly by being pressed into holes that are smaller than the pin diameter. In most applications, the amount of interference has to be limited to keep insertion forces within a practical limit. The acceptable press fit for most metals (steel, brass, and aluminum) is between .0005" and .002". In production assembly, the acceptable press fit is the sum of the tolerances for the pin and the hole. It is for this reason that a very precise and straight hole is required to install these pins, with total tolerances between .0002" and .0005".

To achieve such a precise hole, common machining practice is to drill and ream, but it is not as simple as just that. In order to ream a precise hole, you need to begin with a good quality drilled hole. A reamer will not correct a bell-mouthed, out-of-round, crooked, oversized or badly chattered hole. The quality of drilled hole required prior to reaming is of the same quality required for the use of a solid knurled or grooved pin.



2. Knurled & Grooved Pins

Knurled pins and grooved pins are solid cylindrical pins that have raised longitudinal “ridges” along the length of the pin, which are larger than the cylindrical pin body. The hole is sized to be larger than the body of the pin, yet smaller than the raised knurls or grooves. Keeping the body of the pin smaller than the hole decreases insertion forces. The knurls or grooves serve as the interference portion of the pin in the hole, for press fit applications. The difference in diameter between the pin body and raised “ridges” allows for greater hole tolerances in the assembly than with ground dowels or straight pins.

The common machining practice to achieve the recommended hole tolerances required of knurled and grooved pins, is a quality drilled hole. A prerequisite to producing any quality hole is having rigid control of the work piece. This requirement becomes more critical in difficult to machine materials, as well as with small diameter tools. Even slight movements of the work piece while machining will hinder creation of a quality hole.

Drilling a quality hole will almost always include the use of a spot or center drill prior to drilling, unless a core hole exists, as may be the case with a casting. Spot drilling prior to hole drilling prevents the drill from “walking” on its point, prior to the outer edges of the drill cutting the host material. This practice will help produce a hole that is straight and closer to the diameter of the drill.

When producing holes in surfaces that are not flat, or not perpendicular to the drilled hole to be produced, it is often necessary to use a drill bushing to produce a straight and true hole. A drill bushing may also be necessary when drilling deep holes to keep the drill from flexing while machining. It is recommended that the shortest drill available to produce the hole be used, as the increased rigidity will improve hole accuracy and tool life.

The use of a proper cutting fluid, as well as the proper speeds and feeds per the drill manufacturer’s recommendation or a machinist’s handbook, will help produce a quality hole and extend the life of the drill. Carbide tooling and coatings should be utilized whenever practical and keeping the drill sharp is a must. For sharpened drills, it is important that the cutting lips are of equal length and angle, or the drill will walk.



3. Slotted Spring Pins

Slotted spring pins are hollow tubular parts, chamfered on the ends with a single longitudinal slot along the length of the pin. The pin is retained in the assembly by compressing as it is installed into a hole, which is smaller than the body of the pin. The slot provides room for the pin to compress, and the spring characteristic of the pin’s material provides the resistance that keeps the pin in the hole. If the pin were to “butt” during installation, the insertion forces would increase significantly, as the pin no longer functions as a spring but as a solid object. This spring characteristic of the pin, in conjunction with the slot, allows for greater hole tolerances in the assembly than with solid pins.

Slotted spring pins are designed to be installed in common drilled holes. In addition to their greater allowable hole diameter tolerance, it is not critical that the holes be straight or round, due to the pin’s ability to conform to the hole. The relaxed hole requirements allow these pins to be successfully utilized in as-cast, as-molded or stamped holes. Although it is usually not necessary to use the hole preparation methods previously described, a more consistent hole will improve the repeatability of insertion and retention values in the assembly.

In stamped holes it is recommended that the pins are installed in the same direction as the punch, and excessive burrs should be avoided. Cast or sintered holes should be created with a slight lead-in radius, and the edges of holes in hardened materials should be deburred. These provisions will aid in the successful installation of any spring pin. A countersink does not eliminate the sharp edge of a hardened hole; it merely places a sharp edge deeper into the hole.



4. Coiled Spring Pins

Coiled spring pins are hollow tubular parts produced from 2-1/4 coils of spring steel with swaged chamfered ends. The pin is retained in the assembly by compressing as it is installed into a hole, which is smaller than the body of the pin. The pin coils within itself under compression, and the spring characteristic of the pin's material provides the resistance that keeps the pin in the hole. Due to the 2-1/4 coil design of the pin it cannot "butt" when installed into a minus tolerance hole. The pin maintains its spring characteristic; thus having the lowest installation force of all press fit fasteners. The ability to be installed into a minus tolerance hole, allows for greater hole tolerances in the assembly than other spring pins.

As with other spring pins, coiled spring pins are designed to be installed in common drilled holes. It is not critical that the holes are straight or round, and this pin is the most successful in as-cast, as-molded or stamped holes. The pin's ability to install into a minus tolerance hole allows the use of standard drills in materials which tend to cut undersized. The use of methods previously described for a quality drilled hole will improve the repeatability of insertion and retention values in the assembly, although not required.

In stamped holes it is recommended that the pins are installed in the same direction as the punch, and excessive burrs should be avoided. Cast or sintered holes should be created with a slight lead-in radius, and the edges of holes in hardened materials should be deburred. These provisions will aid in the successful installation of any spring pin. A countersink does not eliminate the sharp edge of a hardened hole; it merely places a sharp edge deeper into the hole.

Coiled spring pins have the largest recommended hole tolerance of all press fit pins. This allows the pin user more freedom in the selection of the hole preparation method, resulting in the lowest prepared hole cost.

ISO/TS 16949 Certified
ISO 9001 Certified

© 2002-2017 SPIROL International Corporation

No part of this publication may be reproduced or transmitted in any form or by any means, electronically or mechanically, except as permitted by law, without written permission from SPIROL International Corporation.

Technical Centres

Europe SPIROL United Kingdom
17 Princewood Road
Corby, Northants
NN17 4ET United Kingdom
Tel. +44 1536 444800
Fax. +44 1536 203415

SPIROL France
Cité de l'Automobile ZAC Croix Blandin
18 Rue Léna Bernstein
51100 Reims, France
Tel. +33 3 26 36 31 42
Fax. +33 3 26 09 19 76

SPIROL Germany
Ottostr. 4
80333 Munich, Germany
Tel. +49 89 4 111 905 71
Fax. +49 89 4 111 905 72

SPIROL Spain
08940 Cornellà de Llobregat
Barcelona, Spain
Tel. +34 93 669 31 78
Fax. +34 93 193 25 43

SPIROL Czech Republic
Sokola Tůmy 743/16
Ostrava-Mariánské Hory 70900
Czech Republic
Tel/Fax. +420 417 537 979

SPIROL Poland
ul. Solec 38 lok. 10
00-394, Warszawa, Poland
Tel. +48 510 039 345

Americas SPIROL International Corporation
30 Rock Avenue
Danielson, Connecticut 06239 U.S.A.
Tel. +1 860 774 8571
Fax. +1 860 774 2048

SPIROL Shim Division
321 Remington Road
Stow, Ohio 44224 U.S.A.
Tel. +1 330 920 3655
Fax. +1 330 920 3659

SPIROL Canada
3103 St. Etienne Boulevard
Windsor, Ontario N8W 5B1 Canada
Tel. +1 519 974 3334
Fax. +1 519 974 6550

SPIROL Mexico
Avenida Avante #250
Parque Industrial Avante Apodaca
Apodaca, N.L. 66607 Mexico
Tel. +52 81 8385 4390
Fax. +52 81 8385 4391

SPIROL Brazil
Rua Mafalda Barnabé Soliane, 134
Comercial Vitória Martini, Distrito Industrial
CEP 13347-610, Indaiatuba, SP, Brazil
Tel. +55 19 3936 2701
Fax. +55 19 3936 7121

Asia Pacific SPIROL Asia Headquarters
1st Floor, Building 22, Plot D9, District D
No. 122 HeDan Road
Wai Gao Qiao Free Trade Zone
Shanghai, China 200131
Tel. +86 21 5046 1451
Fax. +86 21 5046 1540

SPIROL Korea
160-5 Seokchon-Dong
Songpa-gu, Seoul, 138-844, Korea
Tel. +86 21 5046-1451
Fax. +86 21 5046-1540

email: info-uk@spirol.com

SPIROL.co.uk